




Full Gigabit
Ports




Smart PoE
Support



IP65
Waterproof



Wall/Pole
Installation



Plug & Play



Fiber
Connectivity

6-Port Gigabit Outdoor PoE Switch with 2-Port SFP

Introduction

MokerLink POE-G042GSO Outdoor PoE Switch provide you a quick, easy way to deploy outdoor cameras or APs over long distances. You can place the device at outdoor environment without concern of water damage and provide fast network and sufficient high power. With an integrated SFP port, it's perfect for fiber-based installation.

Key Features

- Support IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at
- Provides 4*10/100/1000M PoE ports
- Provides 2*1000M SFP ports
- 100-240VAC Input
- High back-plane bandwidth 12Gbps
- Outdoor rain proof case

6-Port Gigabit Outdoor PoE Switch with 2-Port SFP

Secification

I/O Interface	
Power	Input: AC Input (100-240V)
Ethernet	6* 10/100/1000M PoE Ethernet Ports 2* 1000M SFP Ports
Performance	
Bandwidth	1.2Gbps
Pack forward rate	893Kpps
Memory Cache	448K
MAC Address	1K
Jumbo Frame	9216bytes
Transfer Mode	Store and forward
Standard	
Network Protocol	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3ab (Gigabit Ethernet) IEEE802.3x (Flow Control) IEEE 802.3z (Gigabit Ethernet Fiber Standard)
PoE Protocol	IEEE802.3af(15.4W) IEEE802.3at(30W)
PoE Pin Assignment	V- (RJ45 Pin1,2), V+ (RJ45 Pin 3,6)
Network Medium	10Base-T : Cat3, 4, 5or above UTP(≤100m) 100Base-TX : Cat5 or above UTP(≤100m) 1000Base-TX : Cat5 or above UTP(≤100m)
Optical Medium	Multimode optical fiber: 50/125, 62.5/125, 100/140um Single-mode optical fiber: 8/125, 8.7/125, 9/125, 10/125um
Certification	
Safety Certificate	CE, FCC, RoHS
Environment Standard	
Working Environment	Working Temperature: -20~60°C Storage Temperature: -20~70°C Working Humidity: 10%~90%, non-condensing Storage Temperature: 5%~90%, non-condensing
Function Indicator	
Indicator	PWR (Power), 1-6 Green Light (Link&Data) 1-4 Green Light (PoE)
PWR	On: Powered on Off: Powered off
1-6 Green Light (Link&Data)	On: Link normal Off: Link blocked Flashing: Data transmitting

6-Port Gigabit Outdoor PoE Switch with 2-Port SFP

Physical Structure

Structure Size	Product Dimensions: 295*205*50mm Package Dimensions: 510*280*100mm Product N.W: 0.90kg Product G.W: 1.35kg
----------------	---

Power Voltage	Input voltage :AC100-240V Power supply: 52V 1.25A (65W)
---------------	--

Packing List	Switch 1 PC, Power cord with terminal 1 PC, User manual 1 PC
--------------	--